

## RPRO2

The reader is a wall-mounted access control device used for easy access with smartphones or other credentials.

- Key features
- Mobile and physical credentials
- Tamper alerts
- Visual and audio feedback for unlock events
- Offline Mode
- Connectivity via PoE or low voltage + WiFi

### Credentials

- Standardized credentials, including Bluetooth, NFC and RFID
- Bring your current badges or adopt new ones
- Smartphones, Kisi Passes, cards, and fobs



\*Kisi Passes are 128bit AES encrypted cards that are based on the MiFare De sFire EV1 card platform.

### Features

Operating temperature  
 -4°F to 185°F (-20°C to 85°C)  
 Weather resistant

Operating Voltage  
 12/24 VDC  
 Power over Ethernet

Operating Current  
 0.7A @ 12VDC  
 0.4A @ 24VDC  
 0.3A @ PoE

WiFi  
 2.4/5 GHZ  
 802.11 a/b/g/n

Ethernet  
 10/100 Mbps

Cryptographic support  
 Increased Security

Bluetooth  
 Bluetooth 4.2

User feedback  
 LED signaling  
 Buzzer

NFC  
 13.56 Mhz  
 Cards and fobs

RFID  
 125 kHz  
 Cards and fobs  
 Formats supported:  
 • HID 26-bit (H10301)  
 • HID 37-bit (H10302)  
 • HID 37-bit (H10304)  
 • HID Corporate 1000 35-bi

Measurements (inches)  
 Height: 4.84"  
 Width: 1.97"  
 Depth: 0.61"

[Learn more](#)

[Wiring diagram](#)

[getkisi.com](http://getkisi.com)



45 Main Street,  
 11201 Brooklyn  
 USA

sales@getkisi.com  
 getkisi.com